

Significant Features

More Reliable

- 2 year warranty – twice as long as others

More Efficient

- Works effectively in rooms as cool as 38°F
- Meets ENERGY STAR® standards, saving on energy costs

Easier to Use

- Easy-carry handle for portability
- Easy slide-out bucket design makes emptying a breeze
- Auto shut-off stops collecting water when full
- Washable, removable filter for easy maintenance

Quite & Relaxing

- Quiet operation for a relaxing environment



The Hisense DH5023KP Dehumidifier is designed to fit in small spaces and can remove up to 50 pints of moisture at a time from rooms as large as 300 sq. ft. It is designed to work in a cool environment as low as 38°F, which is just right for unheated garages and basements. The easy-carry handle makes it easy to move from room to room, and an automatic shut-off feature helps prevent accidental overflow. Its efficient design meets ENERGY STAR® requirements and provides quiet operation.

Model #	DH5023KP
Performance	
Dehumidification(Pints/ 24 hours)	50 pints
IEF (65 °F)	1.8
Coverage	Up to 4500 sq ft
Refrigerant	R-410A
Noise Level in dB	45-48 dB
Electrical	
Voltage / Freq / Amps	115V/ 60Hz/ 4.9A
General Features	
Unit Control Type	Electronic
Fan Control	Button
Adj. Humidity Control	YES
Display Type	YES
Continuous Run	YES
Auto Dry	YES
Manual Setting	30% - 80%
Timer-Clock	YES
Fan Speeds	3 Speeds (Lo, Hi, Auto)
Pump Mode	YES
Refrigeration Compartment	
Auto Bucket Shutoff	YES
Garden Hose Connection	Standard Garden Hose
Washable Filters	Yes, Easy Access
Max Pump Discharge Height	16 feet (head)
Accessories	
Quick Connect Hose	Yes. included (9mm dia.)
Approvals	
Safety	UL
Energy Star	YES

Product Dimensions	
Unit Dimension WxDxH (mm)	384 X 272 X 629
Net Weight (Kg)	18.9
Unit Dimension W x D x H (inch)	15.1 X 10.7 X 24.8
Net Weight (lbs)	41.7
Product	
Parts & Labor	2 years
UPC	819130029139

Note:

Product Images

Control Panel



Draining hose with Quick Connector (included)

Bucket conveniently located on front with handle for easy emptying



All product, product specifications, and data are subject to change without notice to improve reliability, function, design or otherwise. ©2020 Hisense USA, All rights reserved

Hisense USA Corporation
7310 McGinnis Ferry Road, Suwanee, GA, 30024
1-888-935-8880
www.hisense-usa.com